



PACKAGING

## PROTECTIVE MASKING PAPER FOR PAINTING PROCESSES



### COMPOSITION

- ▶ Virgin Kraft paper
- ▶ Recycled paper available

### QUALITY OF PRODUCT

- ▶ Very low porosity
- ▶ Barrier for use during the paint process
- ▶ In choosing Kraft paper, you benefit from high mechanical properties of resistance
- ▶ Can be moulded to specific shapes
- ▶ Can be used with all adhesives

### APPLICATION USE

- ▶ Car frame spray painting
- ▶ Building painting
- ▶ Spare parts painting

### PALLETIZATION

- ▶ Standard sizes : 450 mm, 700 mm, 900 mm, 1200 mm
- ▶ Available in rolls
- ▶ Custom sizes available upon request

## SPECIFICATION SHEET

			Standards
Weight		40 g/sqm	ISO 536
Tensile strength	MD	50 N	ISO 1924-2
	CD	25 N	ISO 1924-2
Burst index		3.5 kPa.sqm/g	ISO 2758
Bendtsen porosity		140 ml/min	ISO 5636-3
COBB 60 sec.		≤ 30 g/sqm	ISO 535



TECHNICOAT  
*Solution*

solution@cgp-coating.com - www.cgp-coating.com

