



LOGISTIC

STABUMAX 500

ANTI-SLIP FLOOR MAT



COMPOSITION

- ▶ Anti-slip coating (top side)
- ▶ Board
- ▶ Anti-slip coating (bottom side)

QUALITY OF PRODUCT

- ▶ Aggressive non-slip/ Very high coefficient of friction
- ▶ Easy to use / Save man hours during loading procedures
- ▶ Thickness does not influence height of skid
- ▶ **100% recyclable**

APPLICATION USE

- ▶ Cargo securement anti-slip floor mats in transports, trains and containers
- ▶ Stowing option to increase product stability on floor bed
- ▶ Reduces the strapping required
- ▶ Successful for all product goods : pallets, over-sized cargo, paper rolls...

PALLETIZATION

- ▶ Standard pallet sheet sizes (1000 sheets/pallet)
- ▶ Custom sheet sizes available

SPECIFICATION SHEET

Paper type	Recycled board			Standards
Weight	500 g/sqm			ISO 536
	Stabumax on Paper	Standard	Stabumax on wooden pallet	
Slide angle	≥ 65°	NF Q 03-083	N/A	N/A
Static coefficient of friction	≥ 2	ISO 8295	≥ 0,9	VDI 2700-14
Dynamic coefficient of friction	≥ 0,6	ISO 8295	≥ 0,5	VDI 2700-14

