



LOGISTIC

STABULON®

ANTI-SLIP TIE-SHEET

COMPOSITION

- ▶ 2 Sides coated material
- ▶ (FSC® paper, cardboard & corrugated)

QUALITY OF PRODUCT

- ▶ High non-slip properties
- ▶ **100% recyclable**
- ▶ Tertiary packaging, indirect food contact

APPLICATION USE

- ▶ **Stabilize any packaging format** (box, paper & plastic bags, trays, shrink packs, big bags...)
- ▶ Manual handling
- ▶ Automated end-of-line palletization

KEY ADVANTAGES

- ▶ Secure all logistics operations
- ▶ Optimize secondary & tertiary packaging materials

DIMENSIONS

- ▶ Euro-pallet
- ▶ UK-pallet
- ▶ Half pallet
- ▶ Customized sizes



www.communication.02.48.28.47.82 Photo: © Eric Leguery / BILCOG/Univ4



TYPE	GRAMMAGE	QUANTITY PER PALLET	FORMAT	PERFORMANCE*
PAPER	STABULON® 100	5000	SHEETS & ROLLS	Slide angle NF Q 03-083 ≥ 42 ° Stabulon® on Paper
	STABULON® 140	4000	SHEETS & ROLLS	
	STABULON® 220	3000	SHEETS & ROLLS	
	STABULON® 300	2000	SHEETS & ROLLS	
WATERPROOF PAPER	STABULON® OCEAN 160	3000	SHEETS & ROLLS	Static Coefficient of friction ISO 15 359 0,6 Stabulon® on Paper
	STABULON® OCEAN 280	2000	SHEETS & ROLLS	
SOLID BOARD	STABULON® 450	1600	SHEETS	Dynamic Coefficient of friction ISO 15 359 0,5 Stabulon® on Paper
	STABULON® 600	1200	SHEETS	
	STABULON® 800	1000	SHEETS	
CORRUGATED BOARD	STABULON® E400	700	SHEETS	*characteristic of the ag support before transformation (corrugation, etc.)
	STABULON® B400	380	SHEETS	
	STABULON® B 600	350	SHEETS	

Measurements carried out in accordance with standard NF Q03-083. The results depend on the load to be stabilized and the load-dependent friction properties. The coefficient of friction is given as an indication. An evaluation in real conditions may be necessary to validate the product.



TECHNICOAT
Solution

solution@cgp-coating.com - www.cgp-coating.com